



Flexible Expansion

Up to 10 units in parallel, 10.24kWh--102.4kWh capacity



Easy Installation

Support wall-mounted, floor-mounted installations, high space utilization



IP65 Protection

Fearless of outdoor insatallition, strong environmental adaptability



Battery Equalization

Support extreme mixing of modules at 0% and 100% charge



All-round Safety

Short-circuit lockout, surge-resistant, safe and reliable

Model	Powerbox Pro
Battery Type	LiFePO₄
Nominal Battery Energy	10.24 kWh
Operating Voltage	44.8~57.6V
Nominal Voltage	51.2V
Nominal Capacity	200Ah
Nominal Power	5.12kW
Peak Power	10.24kW
Recomended Charge & Discharge C Rate	0.5C
Recommended Charge/Discharge Current	100A
Recommended Depth of Discharge (DOD)	90%
Net Weight	103kg
Dimension[W/D/H]	555/210/928 mm
Charging Temp. Range	0~55°C
Discharging Temp. Range	-20~55°C
Communication	CAN/RS485
WiFi Module	Optional
Cycle Life *	≥6000 Cycles
Protection Level	IP65
Expansion	Up to 10 units in parallel
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619/IEC62040/UKCA/CEC
Compatible Inverters	SMA/Schneider/Victron energy/Ingeteam/Solis/GoodWe/Growatt/Soplanet/Luxpower/DEYE etc.

^{*} Test conditions: 0.2C Charging & Discharging. @25°C, 90% DOD

